

1500 bar Two Outlet Manifold Block with Manual Stop Valves

The maximum working pressure for this two outlet Manifold Block with Stop Valves is 1500 bar. The manifold is assembled with self sealing quick connectors for fast and clean operation. The inlet is fitted with a quick connect male nipple. The two outlets are fitted with quick connect female couplings

Each manifold block is filled with oil and pressure tested prior to despatch. Test certificates are supplied. All manifolds are identified by serial numbers.

The manifold conforms to the requirements of the European Pressure Equipment Directive and is CE marked

The quick connectors are fitted with plastic dust caps. Each manifold block is filled with oil and pressure tested prior to despatch. Test certificates are supplied. All manifolds are identified by serial numbers. The manifold conforms to the requirements of the European Pressure Equipment Directive and is CE marked.



Two tool outlets via self sealing quick connect coupling, fitted with plastic dust caps

Two outlets controlled by manually operated stop valves



Inlet from pump via self sealing quick connect nipple fitted with a plastic dust cap

CE Marked

Part No BT-1571

BOLTIGHT
HYDRAULIC BOLT TENSIONING
BOLTIGHT is the UK Registered Trade Mark of Boltight Limited

Boltight Limited, Unit 2, Junction 10 Business Park, Bentley Mill Way, Walsall, West Midlands, WS2 0LE, United Kingdom.
Tel: +44 (0)845 500 5556 Fax no. +44 (0)845 500 5557
email: sales@boltight.com www.boltight.com