



2500 bar Electric Driven Power Pack

The BT-2506-E electric motor driven power pack is designed for use with all 2500 bar tooling. It allows pressures of up to 2500 bar to be reached very quickly giving significant time saving in assembly operations.

BT-2506-E is a high specification pump suitable for large groups of tools, and faster required flow rates and operating times.

With optional PLC control and automatic pressure setting the BT-2506-E high flow power pack is fully programmable and allows the operator to view certain types of system data such as input status or timer values. The unit can also be connected to a PC for full traceability.

Combined with full pendant control this pump is particularly suitable for OEM and factory use. Versions for operating pressures up to 3000 bar also available.

Specification

Working Pressure
2500 bar (36000 psi)

Oil Output Flow Rates
Max. flow 8.4 litres per min

Electric Motor Options
Single/Three Phase 110V/220V/380V

Dimensions
500 mm long x 370 mm wide x 470 mm high

Weight
50 kg

Oil Reservoir
7 (4 usable) litre tank capacity

Pressure Gauge
110 mm analogue gauge

Features
- Constant pressure operation
- Quite operation 64dB (A)
- Compact unit
- PLC Programmable
- Full pendant control
- Comprehensive operating manual
- CE marked





This pump conforms to the European Pressure Equipment Directive and is CE Marked

BOLTIGHT
HYDRAULIC BOLT TENSIONING
BOLTIGHT is the UK Registered Trade Mark of Boltight Limited

Boltight Limited, Unit 2, Junction 10 Business Park, Bentley Mill Way, Walsall, West Midlands, WS2 0LE, United Kingdom.
Tel: +44 (0)845 500 5556 Fax no. +44 (0)845 500 5557
email: sales@boltight.com www.boltight.com