



3000 bar Air Driven Power Pack

This easy to use, air driven hydraulic pump is mounted in a tubular steel transportable frame painted red. The pack is supplied complete with, air inlet connector, air filter, air pressure regulator, air lubricator, air pressure gauge, air pressure limit valve, pump on/off control, oil reservoir, oil pressure release valve, oil pressure gauge, gauge guard, air/hydraulic pump and high pressure oil outlet through a self sealing quick connect coupling type D.

BT-3007 is designed for use with all Boltight 3000 bar tooling and represents the best compromise between price and performance.

Pumps for 1000 bar, 1500 bar, 2000 bar and 2500 bar working pressures are also available.
Custom built power packs with any number of outlets, to suit your existing tooling or with special features are available on request.

Specification

Consumption of Free Air
1600 litres per minute (56 standard cubic feet per minute)

Air Pressure Required
7 bar (100 psi)

Dimensions
400 mm long x 400 mm wide x 440 mm high

Weight
23 kg

Oil Reservoir
8.5 litre ISO 10 hydraulic oil

Finish
Red Paint Hammer Finish


Pressure Gauge
Dual Scale 0 - 3500 bar (0 - 50000 psi)

Working Pressure
3000 bar

Oil Flow Rate
See graph



Air Driven Power Pack



BT-3007

This pump conforms to the European Pressure Equipment Directive and is CE Marked

BOLTIGHT
HYDRAULIC BOLT TENSIONING
BOLTIGHT is the UK Registered Trade Mark of Boltight Limited

Boltight Limited, Unit 2, Junction 10 Business Park, Bentley Mill Way, Walsall, West Midlands, WS2 0LE, United Kingdom.
Tel: +44 (0)845 500 5556 Fax no. +44 (0)845 500 5557
email: sales@boltight.com www.boltight.com